


Chapter 12
Described Auditory Content – Music

The Design and Implementation of
Multimedia Software

David Bernstein

Jones and Bartlett Publishers

www.jbpub.com




About this Chapter

- Described Auditory Content:
Described speech, described sounds, and described music
- This Chapter – Described Music:
‘Name’ frequencies.

Describe the duration of individual sounds.


Describe the ‘voice’ or ‘instrument’.

Describe the loudness of those sounds.





Musical Instrument Digital Interface (MIDI)

- Original Purpose:
A protocol for passing musical events between electronic instruments and sequencers.
- Our Interest:
Sending messages to a sound card.




The Sequence, Track and MidiEvent Classes



Reading MIDI Events from a File

1. Create a `Sequence` from a `File` or an `InputStream`.
2. Create a `Sequencer`.
3. Open the `Sequencer`.
4. Associate the `Sequence` with the `Sequencer`.
5. Start the `Sequencer`.



MidiPlayer


```
import java.io.*;
import javax.sound.midi.*;

public class MidiPlayer
{
    public static void main(String[] args) throws Exception
    {
        Sequencer          sequencer;
        Sequence            seq;

        seq = MidiSystem.getSequence(new File(args[0]));

        sequencer = MidiSystem.getSequencer();
        sequencer.open();

        sequencer.setSequence(seq);
        sequencer.start();
    }
}
```




Requirements



F12.1 Encapsulate a description of music.

F12.2 Present/render this description.




Ways Synthesizers Can Generate Signals

- Using a Soundbank:

The synthesizer has a database of ‘sounds’ (e.g., samplings of different instruments producing different tones) that it uses to produce the electrical signal.

- Using Waves:

The synthesizer constructs the electrical signals from continuous waves.




Rendering in Java

- **Synthesizer:**

Controls a set (typically with 16 members) of `MidiChannel` objects that encapsulate ‘voices’.


- **Setup:**

1. Obtain a `Synthesizer` object by calling the `MidiSystem.getSynthesizer()` method.
2. Get a `Soundbank` object (e.g., by calling the `Synthesizer` object’s `getDefaultSoundBank()` method).
3. Call the `Synthesizer` object’s `loadAllInstruments()` method (passing it the `Soundbank` object).
4. Get the `MidiChannel` objects by calling the `Synthesizer` object’s `getChannels()` method.




Rendering Notes – Alternative 1

1. Obtain a **Receiver** object by calling the **Synthesizer** object's `getReceiver()` method.
2. Construct a **ShortMessage** object that turns the note on.
3. Call the **Receiver** object's `send()` method (passing it the **ShortMessage** object).
4. Wait the appropriate amount of time.
5. Construct a **ShortMessage** object that turns the note off.
6. Call the **Receiver** object's `send()` method (passing it the **ShortMessage** object).



Rendering Notes – Alternative 2

1. Call the `MidiChannel` object's `noteOn()` method.
2. Wait the appropriate amount of time.
3. Call the `MidiChannel` object's `noteOff()` method.



Evaluating the Alternatives

Which is better?



Evaluating the Alternatives

The second method is used here because it is simpler and provides all of the necessary functionality.



Naming Frequencies

- Modern Music Notation:


The frequencies in a single octave are denoted by the letters A-G.

Letters can be followed by either a sharp indicator (i.e., a # character) which denotes a half-step or half-tone up, or flat indicator (i.e., a b character) which denotes a half-step or half-tone down.

A complete octave contains A, A#, B, C, C#, D, D#, E, F, F#, G, and G#.


- A Common Tuning:

“A” is the name commonly given to the frequencies 55Hz, 110Hz, 220Hz, 440Hz, 880Hz, 1760Hz, etc.




Describing Durations

- Durations are commonly given as multiples/fractions of a base duration, or *beat*.
- Common durations are whole notes, half notes, quarter notes, eighth notes and sixteenth notes.
- A standard duration can be ‘dotted’ to indicate that it should be increased by 50%.
- *Triplets* are notes that are grouped in sets of three (i.e., the three notes evenly divide an integral number of beats).




Alternative 1




What are the shortcomings?




Alternative 1




It will probably result in code duplication.




Alternative 2 


What are the shortcomings?




Alternative 2




Makes it difficult to add content that is not a specialization of the `AbstractContent` class.




Alternative 3




What are the advantages?




Alternative 3



One can create other classes that implement the `Content` interface without having to specialize the `AbstractContent` class (e.g., a `BrokenChord` class).




Alternative 4 – Composite Pattern



What are the shortcomings?



Alternative 4 – Composite Pattern



It is not consistent with the way the term “chord” is normally used in music theory.



Content

```
package auditory.described;


import javax.sound.midi.*;

public interface Content
{
    public abstract int  getType();

    public abstract boolean isDotted();

    public abstract void render(MidiChannel channel);

    public abstract void setAudible(boolean audible);
}
```



AbstractContent – Structure


```
package auditory.described;

import javax.sound.midi.*;

public abstract class AbstractContent
    implements Content
{
    protected boolean    audible, dotted, playing;
    protected int        type;

    public AbstractContent()
    {
        this(1, false);
    }

    public AbstractContent(int type, boolean dotted)
    {
        this.type    = type;
        this.dotted  = dotted;
        this.audible = false;
        this.playing = false;
    }
}
```



AbstractContent – Getters

```
public int getType()
{
    return type;
}

public boolean isDotted()
{
    return dotted;
}
```




AbstractContent – Setters

```
public void setAudible(boolean audible)
{
    this.audible = audible;
}


protected void setDotted(boolean dotted)
{
    this.dotted = dotted;
}

protected void setType(int type)
{
    this.type = type;
}
```



AbstractContent – Rendering

```
public void render(MidiChannel channel)
{
    if      (audible && !playing)
    {
        playing = true;
        startPlaying(channel);
    }
    else if (!audible && playing)
    {
        playing = false;
        stopPlaying(channel);
    }
}
protected abstract void startPlaying(MidiChannel channel);
protected abstract void stopPlaying(MidiChannel channel);
```



Note – Structure

```
package auditory.described;

import javax.sound.midi.*;

public class Note
    extends AbstractContent
{
    private boolean        sharp;
    private char           pitch;
    private int            midiNumber;

    public Note()
    {
        this('C', false, 0, 1, false);
    }

    public Note(char pitch,    boolean sharp, int octave,
                int type, boolean dotted)
    {
        super(type, dotted);


        this.pitch = Character.toUpperCase(pitch);
        this.sharp = sharp;
        midiNumber = MidiCalculator.numberFor(pitch, sharp, octave);
    }
}
```



Note – Rendering

```
protected void startPlaying(MidiChannel channel)
{
    channel.noteOn(midiNumber, 127);
}

protected void stopPlaying(MidiChannel channel)
{
    channel.noteOff(midiNumber, 127);
}
```



MidiCalculator

```


package auditory.described;

public class MidiCalculator
{
    public static int numberFor(char    pitch,
                               boolean sharp,
                               int     octave)
    {
        int    midiBase, midiNumber;

        // Handle special cases (B sharp and E sharp)
        if ((pitch == 'B') && sharp)
        {
            pitch = 'C';
            sharp = false;
        }
        else if ((pitch == 'E') && sharp)
        {
            pitch = 'F';
            sharp = false;
        }

        // Calculate the MIDI value
        midiBase = 60;
        if    (pitch == 'A') midiNumber = midiBase + 9;
        else if (pitch == 'B') midiNumber = midiBase + 11;
        else if (pitch == 'C') midiNumber = midiBase + 0;
    }
}

```




MidiCalculator (cont.)

```
else if (pitch == 'D') midiNumber = midiBase + 2;
else if (pitch == 'E') midiNumber = midiBase + 4;
else if (pitch == 'F') midiNumber = midiBase + 5;
else if (pitch == 'G') midiNumber = midiBase + 7;
else
    midiNumber = -1; // Rest

if (sharp) midiNumber = midiNumber + 1;

midiNumber = midiNumber + (octave * 12);

return midiNumber;
}
}
```



Chord – Structure

```
package auditory.described;

import java.util.*;
import javax.sound.midi.*;


public class Chord
    extends AbstractContent
{
    private ArrayList<Note> notes;

    public Chord()
    {
        this(1, false);
    }

    public Chord(int type, boolean dotted)
    {
        super(type, dotted);

        notes = new ArrayList<Note>();
    }


    public void addNote(Note note)
    {
        notes.add(note);
    }
}
```



Chord – startPlaying()

```
protected void startPlaying(MidiChannel channel)
{
    Iterator<Note>    i;
    Note              note;


    i = notes.iterator();
    while (i.hasNext())
    {
        note = i.next();
        if (note != null)
        {
            note.setType(type);
            note.setDotted(dotted);
            note.startPlaying(channel);
        }
    }
}
```



Chord – stopPlaying()


```
protected void stopPlaying(MidiChannel channel)
{
    Iterator<Note>    i;
    Note             note;

    i = notes.iterator();
    while (i.hasNext())
    {
        note = i.next();
        if (note != null)
        {
            note.stopPlaying(channel);
        }
    }
}
```



Music Notation

Music notation consists of one or more *staves* (a set of five horizontal lines) that contain multiple measures (delimited by *bar lines*), each of which contains multiple notes (that indicate both the pitch and the duration). The end of a song is usually indicated with a double bar line.




Eight Measures of Beethoven's "Ode to Joy"

Violin



Piano




A More Convenient Notation

A comma delimited **String** with a field for the ‘name’ including an optional ‘#’ character, the octave (with 0 being the octave that contains middle C), the type of the note (i.e., 1 for whole, 2 for half, 4 for quarter, etc) which includes an optional ‘.’ character.



Eight Measures of Beethoven's 'Ode to Joy'

.	.	.	.
.	.	.	.
.	.	.	.
F#,-1,4	D ,-1,4	F#,-1,4	D ,-1,4
F#,-1,4	D ,-1,4	F#,-1,4	D ,-1,4
G ,-1,4	E ,-1,4	G ,-1,4	E ,-1,4
A ,-1,4	F#,-1,4	A ,-1,4	F#,-1,4
A ,-1,4	F#,-1,4.	A ,-1,4	E ,-1,4.
G ,-1,4	E ,-1,8	G ,-1,4	D ,-1,8
F#,-1,4	E ,-1,2	F#,-1,4	D ,-1,4
E ,-1,4		E ,-1,4	R , 0,4
.	.	.	.
.	.	.	.
.	.	.	.



NoteFactory

```

package auditory.described;

import java.util.*;

null
public class NoteFactory
{
    public static Note parseNote(String s)
    {
        boolean        dotted, sharp;
        char            pitch, sharpChar;
        int             duration, octave, octaveEnd;
        Note            theNote;
        String          durationString, octaveString, token;
        StringTokenizer st;


        st = new StringTokenizer(s, ", ");

        try
        {
            token = st.nextToken();

            // Determine the pitch
            pitch = token.charAt(0);

            // Determine if this is a sharp or a natural
            sharp = false;
            if (token.length() == 2)

```



NoteFactory (cont.)

```

    {
        sharpChar = token.charAt(1);
        if (sharpChar == '#') sharp = true; // ASCII 35
    }

    // Determine the octave (relative to middle C)
    octaveString = st.nextToken();
    octave       = Integer.parseInt(octaveString);

    // Determine the duration (which has an arbitrary length)
    dotted       = false;
    durationString = st.nextToken();
    if (durationString.endsWith(".")) dotted = true;
    duration      = (int)Double.parseDouble(durationString);


    // Construct a new Note
    theNote = new Note(pitch, sharp, octave, duration, dotted);
}
catch (NoSuchElementException nsee)
{
    theNote = null;
}
return theNote;
}
}

```




Scales

- An (ascending) *scale* is a sequence of notes that starts and ends on the same note, moving up in a consistent way.
- A *major scale* is a scale that uses the T-T-S-T-T-T-S pattern when ascending (where T denotes a tone or whole step and S denotes a semi-tone or half step).
- A *minor scale* is a scale that uses the T-S-T-T-S-T-T pattern when ascending.



Scales – The C-Major Scale

C	D	E	F	G	A	B	C
T	T	S	T	T	T	S	



Transposition

- A song that uses the notes from a particular scale is said to be in the *key* of that scale.
- Transposition is an operation that changes a song from one key to another.
- Since the representation used here does not include a *key signature*, that is, all notes include explicit sharps/flats, transposition can be performed directly on the MIDI numbers.




What's Left?

- The `Audition` components of the conceptual model.
- The `AuditionView` component of the conceptual model



Organizing Notes and Chords

- Notes are commonly grouped into durations of equal length, called *measures*.
- The *time signature* indicates how many beats are in each measure (in the ‘numerator’) and which type of note gets a whole beat (in the ‘denominator’).
- A collection of notes/chords ordered over time that is intended to be played by a single instrument (or sung by a single voice) is often called a *part*.
- A collection of parts (for different instruments/voices) is referred to as a *score*.




Alternative 1

- Approach:

Each **Part** has it's own **Metronome** object and renders its content (independently) in its own thread of execution.

- Shortcomings:

What are the shortcomings?




Alternative 1

- Approach:

Each **Part** has it's own **Metronome** object and renders its content (independently) in its own thread of execution.


- Shortcomings:

The different **Part** objects may not stay synchronized since the timing of `handleTick()` messages is not precise.




Alternative 2

- Approach:
Have a single **Metronome** object that synchronizes the **Part** objects.
- **handleTick()** Method:
Determines which **Note/Chord** objects needs to be rendered.



Alternative 2.1

- Approach:
Include an attribute for the instrument in **Part**.
- Shortcomings:
What are the shortcomings?




Alternative 2.1

- Approach:

Include an attribute for the instrument in **Part**.


- Shortcomings:

One can not have the same **Part** object rendered using different instruments.




Alternative 2.2

- Approach:
A `Part` object can be told what instrument to use when its `render()` method is called.
- Advantage:
Adds flexibility at no ‘cost’.



The Design



Part – Structure

```
package auditory.described;

import java.util.*;
import javax.sound.midi.*;

import event.*;

public class Part implements MetronomeListener
{
    private ArrayList<Content>    sounds;
    private double                timeSignatureDenominator,
                                timeSignatureNumerator;
    private int                   millisPerMeasure, stopTime;
    public Part()
    {
        sounds                = new ArrayList<Content>();
    }
}
```



Part – add()


```
public void add(Content c)
{
    if (c != null) sounds.add(c);
}
```



Part – Setters


```
public void setTempo(int millisPerMeasure)
{
    this.millisPerMeasure = millisPerMeasure;
}

public void setTimeSignature(int numerator, int denominator)
{
    this.timeSignatureNumerator = numerator;
    this.timeSignatureDenominator = denominator;
}
```



Part – Global Variables

```
private Content          currentContent,  
                        previousContent;  
private Iterator<Content> iterator;  
private Metronome       metronome; // Not Owned
```




Part – upbeat()

```
public void upbeat(Metronome metronome)
{
    this.metronome = metronome; // For later removal

    iterator      = sounds.iterator();
    currentContent = null;
    previousContent = null;
    stopTime      = -1;

    metronome.addListener(this);
}
```



Part – handleTick()

```
public void handleTick(int millis)
{
    double  beats, millisPerBeat, type;

    if (iterator == null)
        throw(new IllegalStateException("No upbeat()"));

    if (millis >= stopTime)
    {
        if (currentContent != null)
            currentContent.setAudible(false);


        if (iterator.hasNext())
        {
            previousContent = currentContent;
            currentContent  = iterator.next();

            // This calculation needn't really be done each iteration
            millisPerBeat = 1.0/(double)timeSignatureNumerator *
                            millisPerMeasure;

            beats          = (1.0/(double)currentContent.getType()) *
                            (double)timeSignatureDenominator;


            if (currentContent.isDotted()) beats = beats * 1.5;

            stopTime = millis + (int)(beats * millisPerBeat);
        }
    }
}
```



Part – handleTick() (cont.)


```
        currentContent.setAudible(true);
    }
    else
    {
        metronome.removeListener(this);
    }
}
}
```



Part – render()

```
public void render(MidiChannel channel)
{
    if (previousContent != null)
        previousContent.render(channel);

    if (currentContent != null)
        currentContent.render(channel);
}
```



PartFactory

```
package auditory.described;


import java.io.*;

public class PartFactory
{
    public static Part createPart(BufferedReader in)
        throws IOException
    {
        Note          note;
        Part           part;
        String         line;

        part = new Part();

        while ((line = in.readLine()) != null &&
            (!line.equals("X")))
        {
            if (!line.equals(""))
            {
                note = NoteFactory.parseNote(line);
                if (note != null) part.add(note);
            }
        }

        return part;
    }
}
```



PartFactory (cont.)

```
public static Part createPart(String filename)
    throws IOException
{
    BufferedReader    in;

    in = new BufferedReader(new FileReader(filename));

    return createPart(in);
}
```



Score – Structure

```
package auditory.described;

import java.util.*;
import javax.sound.midi.*;

import event.*;

public class Score
{
    private Hashtable<Part, MidiChannel>    channelTable;
    private Hashtable<Part, String>        parts;
    private int                             timeSignatureDenominator,
                                           timeSignatureNumerator,
                                           millisPerMeasure;

    public void addPart(Part part, String instrument)
    {
        parts.put(part, instrument);
    }

    public Enumeration<Part> getParts()
    {
        return parts.keys();
    }

    public String getInstrumentName(Part part)
    {
        return parts.get(part);
    }
}
```



Score – Structure (cont.)

```
public void removePart(Part part)
{
    parts.remove(part);
}
}
```




Score – Setters

```
public void setChannel(Part part, MidiChannel channel)
{
    channelTable.put(part, channel);
}

public void setTempo(int millisPerMeasure)
{
    this.millisPerMeasure = millisPerMeasure;
}


public void setTimeSignature(int numerator, int denominator)
{
    this.timeSignatureNumerator = numerator;
    this.timeSignatureDenominator = denominator;
}
```



Score – upbeat()

```
public void upbeat(Metronome metronome)
{
    Enumeration<Part>      e;
    Part                  part;


    e = parts.keys();
    while (e.hasMoreElements())
    {
        part              = e.nextElement();
        part.upbeat(metronome);
        part.setTimeSignature(timeSignatureNumerator,
                             timeSignatureDenominator);
        part.setTempo(millisPerMeasure);
    }
}
```




Score – render()

```
public void render()
{
    Enumeration<Part>      e;
    MidiChannel           channel;
    Part                  part;

    e = parts.keys();
    while (e.hasMoreElements())
    {
        part      = e.nextElement();
        channel   = channelTable.get(part);
        part.render(channel);
    }
}
```



Orchestra – Demonstration




In examples/chapter:

Orchestra.html

```
java -cp Orchestra.jar OrchestraApplication frerejacques.txt
```

```
java -cp Orchestra.jar OrchestraApplication daytripper.txt
```

```
java -cp Orchestra.jar OrchestraApplication OdeToJoy.txt
```




Orchestra – Structure

```
package auditory.described;

import java.io.InputStream;
import java.net.URL;
import java.util.*;
import javax.sound.midi.*;

import event.*;
import io.*;

public class Orchestra implements MetronomeListener
{
    private Hashtable<String, Instrument>    instruments;
    private Metronome                       metronome;
    private MidiChannel[]                  channels;
    private Score                           score;
}
```



Orchestra – Constructor

```
public Orchestra(Score score) throws MidiUnavailableException
{
    this(score, new Metronome(10));
}

public Orchestra(Score score, Metronome metronome)
    throws MidiUnavailableException
{
    Instrument[]    loaded;
    Soundbank       soundbank;
    Synthesizer     synthesizer;

    this.score      = score;
    this.metronome  = metronome;
    metronome.addListener(this);


    instruments     = new Hashtable<String, Instrument>();

    synthesizer     = MidiSystem.getSynthesizer();
    synthesizer.open();
    soundbank       = synthesizer.getDefaultSoundbank();

    if (soundbank == null) soundbank = findSoundbank();


    synthesizer.loadAllInstruments(soundbank);

    channels        = synthesizer.getChannels();
```



Orchestra – Constructor (cont.)

```
loaded = synthesizer.getLoadedInstruments();
for (int i=0; i<loaded.length; i++)
{
    instruments.put(loaded[i].getName(), loaded[i]);
}
}
```



Orchestra – start()

```


public void start()
{
    Enumeration<Part>          e;
    Instrument                 instrument;
    int                       i;
    MidiChannel               channel;
    String                    name;
    Patch                    patch;
    Part                     part;

    e = score.getParts();
    i = 0;

    while (e.hasMoreElements())
    {
        part          = e.nextElement();
        name         = score.getInstrumentName(part);
        instrument    = instruments.get(name);

        // Have the channel use the appropriate instrument
        if (instrument == null)
        {
            channels[i].programChange(0, 0);
        }
        else
        {
            patch = instrument.getPatch();

```




Orchestra – start() (cont.)

```
        channels[i].programChange(patch.getBank(),
                                patch.getProgram());
    }
    score.setChannel(part, channels[i]);

    score.upbeat(metronome);
}


// Start the metronome
metronome.start();
}
```



Orchestra – handleTick()

```
public void handleTick(int millis)
{
    score.render();

    if (metronome.getNumberOfListeners() == 1)
    {
        metronome.stop();
    }
}
```



ScoreFactory

```
package auditory.described;

import java.io.*;
import java.util.StringTokenizer;
import javax.sound.midi.MidiUnavailableException;


import io.*;

public class ScoreFactory
{
    private ResourceFinder    finder;

    public ScoreFactory()
    {
        finder = ResourceFinder.createInstance();
    }

    public ScoreFactory(ResourceFinder finder)
    {
        this.finder = finder;
    }

    public Score createScore(InputStream is)
        throws IOException,
            MidiUnavailableException
    {
        BufferedReader    in;
        int                denominator, numerator, tempo;
```



ScoreFactory (cont.)

```

Note           note;
Part           part;
Score          score;
String         line, voice;
StringTokenizer st;

in = new BufferedReader(new InputStreamReader(is));

// Read the time signature and tempo
line      = in.readLine();
st        = new StringTokenizer(line, ",/");
numerator = Integer.parseInt(st.nextToken());
denominator = Integer.parseInt(st.nextToken());
tempo     = Integer.parseInt(st.nextToken());


score = new Score();

score.setTimeSignature(numerator, denominator);
score.setTempo(tempo);

while ((voice = in.readLine()) != null)
{
    part = PartFactory.createPart(in);
    score.addPart(part, voice);
}

return score;
}

```



ScoreFactory (cont.)

```
public Score createScore(String filename)
    throws IOException,
        MidiUnavailableException
{
    InputStream      is;

    is = finder.findInputStream(filename);

    return createScore(is);
}
}
```

